Profi GO 12 Front Profi R

Data sheet

Details

- Masonry stove heat-kits based on the well-known Profi-Serie
- 1-sided open combustion chamber
- The outer shell is consisting of 60 mm thick heat storage material for a long-lasting heat release
- Manual combustion air supply
- Hinged door, self-closing
- With 4 flue gas connection options
- Suitable for multiple flue connections
- Integrated sensor seat for the SMR Multi Regulator above the firebox door

Profi GO 12 – Front Profi R

Technical data

Fuel volume min.	5 kg
Fuel volume max.	15 kg
Efficiency	> 80 %
Combustion air requirement	133,9 m^3/h
Recommended length of logs	33 cm
Weight	465 kg

Data for chimney sweep according to DIN EN 13384 (closed operation)

Ceramic flues in storage operation

Flue gas mass flow	36 g/s
Flue gas temperature at the chimney connection	600 °C
Required delivery pressure	8 Pa

Standard

Door hinge on left | Door hinge on right | Wood-burning

Optional

150 mm

Combustion air connector

Accessories

SMR

A+

Energy efficiency class in accordance with (EU) 2015/1186

1. Federal Emissions Control Ordinance Stage 2

Made in Germany

EFA

There may be modifications to the colour and technical details caused by ongoing developments; subject to errors and omissions. Dated: 07/2018

Profi GO 12 Front Profi R

Dimensional drawing

Front view, scale 1:20



Side view, scale 1:20



Top view, scale 1:10



Illustrations are similar. All photos and drawings are protected by copyright. Usage or publication, even of individual details, is only permitted with our authorisation. There may be modifications to the colour and technical details caused by ongoing developments; subject to errors and omissions. Dated: 07/2018

Product data sheet

Regulation (EU) 2015/1186 supplementing Directive 2010/30/EU

	Profi GO 12
Supplier's name:	Camina & Schmid Feuerdesign und Technik GmbH & Co. KG
Supplier's model identifier:	Profi GO 12
Energy efficiency class:	A+
Direct heat output (kW)	12,0
Indirect heat output (kW):	–
Energy efficiency index (EEI):	108,9
Energy efficiency at nominal heat output (%):	82,0
Notes for specific precautions, installation or maintenance:	Please note the reference in the assembly instructions and operating manuals!

There may be modifications to technical details caused by ongoing developments; subject to errors and omissions. Dated: 11/2021

Camina & Schmid Feuerdesign und Technik GmbH & Co. KG
Gewerbepark 18 · 49143 Bissendorf · Phone +49 5402 7010-10 · Fax +49 5402 7010-70
www.camina-schmid.de · info@camina-schmid.de

ENERG
енергия · ενεργεια
Y IJA IE IA

Camina Schmid **Profi GO 12**

A+



12,0
kW

ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

2015/1186