

Ekko R 67(45) s with frame doors

Data sheet

Details

- Fireplace insert, open on two sides
- 67(45)51 – Height 51 cm
67(45)57 – Height 57 cm
- Self-closing door
- Front hinged, side part fixed
- Adjustable lower air washing
- Standard fire box inner lining: white smooth chamotte

Technical data

- | | |
|---|--------------|
| • Nominal heat output | 9 kW |
| • Thermal output range | 3,4 – 9,8 kW |
| • Efficiency | >78 % |
| • Insulation thickness (with wall that does not need to be protected) (based on SILCA® 250KM) | 60 mm |
| • Combustion air connector | Ø 125 mm |
| • Recommend length of logs | 33 cm |
| • Weight | 220 – 260 kg |
| • Heat distribution through the viewing window | 50 % |
| • Heat distribution, convective output | 50 % |

Data for chimney sweep according to DIN EN 13384 (closed operation)

Triple values with nominal heat output

- | | |
|------------------------------|---------|
| • Flue gas mass flow | 9,5 g/s |
| • Flue gas temperature | 330 °C |
| • Required delivery pressure | 12 Pa |

Triple values for calculating ceramic flues (wood fuel)

- | | |
|---|-----------|
| • Firing power | 23,3 kW |
| • Flue gas mass flow | 16,7 g/s |
| • Flue gas temperature upstream of the connecting surface | 347 °C |
| • Required delivery pressure at the flue gas connector | 15 Pa |
| • Combustion air requirement | 93,3 m³/h |
| • Recommended flue length ¹ | 3,5 m |

Data for closed design

- | | |
|--|--------|
| • Minimum heat-emitting surface ² | 3,7 m² |
|--|--------|

¹The information regarding flue lengths is a recommendation and based on the calculation in accordance with TROL 2022 chapter 15. The calculation is based on a medium-heavy design and a flue ratio of 360 cm².

²Average value based on the storage time. Dependent on the material properties and the construction thickness. Mean specific heat distribution = approx. 500 W/m²

There may be modifications to the colour and technical details caused by ongoing developments; subject to errors and omissions. Dated: 08/2025



Ekko R 67(45) with frame doors and hinged front

Standard



Kristall front



Door hinge on left



125 mm
Combustion air connector

Optional



Double glazing



External fuel-door



150 mm
Combustion air connector

Accessories



Heat exchanger



Top mounted heat exchanger



Adera



Energy efficiency class in accordance with (EU) 2015/1186




1. Federal Emissions Control Ordinance Stage 2



Ekko R 67(45) s with frame doors

Dimensional drawing



Product data sheet

Regulation (EU) 2015/1186 supplementing Directive 2010/30/EU

	Ekko L/R 67(45) s/h
Supplier's name:	Camina & Schmid Feuerdesign und Technik GmbH & Co. KG
Supplier's model identifier:	Ekko L/R 67(45) s/h
Energy efficiency class:	A
Direct heat output (kW)	9,0
Indirect heat output (kW):	–
Energy efficiency index (EEI):	103,2
Energy efficiency at nominal heat output (%):	78,1
Notes for specific precautions, installation or maintenance:	Please note the reference in the assembly instructions and operating manuals!


There may be modifications to technical details caused by ongoing developments; subject to errors and omissions. Dated: 11/2021




ENERG
енергия · ενέργεια



Camina  Schmid Ekko L/R 67(45) s/h





9,0
kW

ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

2015/1186