# Pano 67 s

## Data sheet

**Details**

- Fireplace insert, open on one side, Front: Panorama
- 6745 – Height 45 cm
  6751 – Height 51 cm
  6757 – Height 57 cm
- Self-closing door
- Adjustable lower air washing
- Standard fire box inner lining: smooth beige chamotte
- High-grade cast-iron dome, all parts can be moved, adjustable between 0 – 90°
- Overall height can be simply and quickly adjusted
- Easy to dismantle for transport

*Pano 67 with hinged front*

**Technical data**

| | |
|---|---|
| Nominal heat output | 9 kW |
| Thermal output range | 3,3 – 8,7 kW |
| Efficiency | >78 % |
| Insulation thickness (with wall that does not need to be protected) (based on SILCA® 250KM) | 60 mm |
| Combustion air connector | Ø 125 mm |
| Recommend length of logs | 33 cm |
| Weight | 200 – 220 kg |
| Heat distribution through the viewing window | 35 % |
| Heat distribution, convective output | 65 % |

**Data for chimney sweep** according to DIN EN 13384 (closed operation)

**Triple values with nominal heat output**

| | |
|---|---|
| Flue gas mass flow | 7,6 g/s |
| Flue gas temperature | 340 °C |
| Required delivery pressure | 12 Pa |

**Triple values for calculating ceramic flues** (wood fuel)

| | |
|---|---|
| Firing power | – |
| Flue gas mass flow | – |
| Flue gas temperature upstream of the connecting surface | – |
| Required delivery pressure at the flue gas connector | – |
| Combustion air requirement | – |
| Recommended flue length[1] | 1,7 m |

**Data for closed design**

| | |
|---|---|
| Minimum heat-emitting surface[2] | 4,2 m² |

[1] The information regarding flue lengths is a recommendation and based on the calculation in accordance with TROL 2022 chapter 15. The calculation is based on a medium-heavy design and a flue ratio of 360 cm².

[2] Average value based on the storage time. Dependent on the material properties and the construction thickness. Mean specific heat distribution = approx. 500 W / m²

There may be modifications to the colour and technical details caused by ongoing developments; subject to errors and omissions. Dated: 01/2024

**Standard**

Anthracite front

Door hinge on left

Door hinge on right

Combustion air connector

**Optional**

External fuel-door

Combustion air connector

**Accessories**

Heat exchanger

Top mounted heat exchanger

Hot air top-mounted element

Hot water top-mounted element R

SMR

Energy efficiency class in accordance with (EU) 2015/1186

1. Federal Emissions Control Ordinance Stage 2

Made in Germany

EFA

# Pano 67 s

## Dimensional drawing

**Front view, scale 1:20**




**Side view, scale 1:20**




**Top view, scale 1:10**




Illustrations are similar. All photos and drawings are protected by copyright. Usage or publication, even of individual details, is only permitted with our authorisation. There may be modifications to the colour and technical details caused by ongoing developments; subject to errors and omissions. Dated: 07/2018

# Product data sheet

Regulation (EU) 2015/1186 supplementing Directive 2010/30/EU

| | **Pano 67 s/h** |
|---|---|
| **Supplier's name:** | Camina & Schmid Feuerdesign und Technik GmbH & Co. KG |
| **Supplier's model identifier:** | Pano 67 s/h |
| **Energy efficiency class:** | A |
| **Direct heat output (kW)** | 9,0 |
| **Indirect heat output (kW):** | – |
| **Energy efficiency index (EEI):** | 105,0 |
| **Energy efficiency at nominal heat output (%):** | 79,3 |
| **Notes for specific precautions, installation or maintenance:** | Please note the reference in the assembly instructions and operating manuals! |

*There may be modifications to technical details caused by ongoing developments; subject to errors and omissions. Dated: 11/2021*

**Camina & Schmid Feuerdesign und Technik GmbH & Co. KG**
Gewerbepark 18 · 49143 Bissendorf · Phone +49 5402 7010-10 · Fax +49 5402 7010-70
www.camina-schmid.de · info@camina-schmid.de

ENERG
енергия · ενεργεια
Y IJA IE IA

Camina Schmid **Pano 67 s/h**




ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

**2015/1186**