

S23 GO-Line wall connection

Data sheet




Figure: S23 GO-Line with wall connection | Surface finish: Camina silicate paint

Standard	Total weight	Optional	Accessories		Storage concrete	Masonry stove
 hinged door, hinge on left / right  Front Kristall	 kg approx. 630 kg		 SMR	 Spark protection plate	 Storage concrete	 Ekko GO 45(45)57 with rotary chimney Nominal heat output: 2.0 kW Outlet for flue pipe: Ø 160 mm  Energy efficiency class as per (EU) 2015/1186 More information at www.camina-schmid.de


S23 GO-Line wall connection

Dimensional drawing


Front view, scale 1:20




Left side view scale 1:20



Top view, scale 1:20



Screed recess (view of underside) scale 1:20



Note on left side view scale 1:20: AS (FGC): Flue gas connector, **VLS (CAC):** Combustion air connector, **VLZ (CAS):** Combustion air supply, **OKFF (FFL):** Finished floor level

Please note the wall distance of 100 mm and information on **optional accessories** in our price list.

Illustrations are similar. All photos and drawings are protected by copyright. Usage or publication, even of individual details, is only permitted with our authorisation. There may be modifications to the colour and technical details caused by ongoing developments; subject to errors and omissions. Dated: 04/2020

Product data sheet

Regulation (EU) 2015/1186 supplementing Directive 2010/30/EU

	S23 GO-Line (Speicherfeuerstätte)
Supplier's name:	Camina & Schmid Feuerdesign und Technik GmbH & Co. KG
Supplier's model identifier:	S23 GO-Line (Speicherfeuerstätte)
Energy efficiency class:	A+
Direct heat output (kW)	2,0
Indirect heat output (kW):	–
Energy efficiency index (EEI):	115,1
Energy efficiency at nominal heat output (%):	86,3
Notes for specific precautions, installation or maintenance:	Please note the reference in the assembly instructions and operating manuals!

There may be modifications to technical details caused by ongoing developments; subject to errors and omissions. Dated: 11/2021



ENERG
енергия · ενέργεια




Camina  Schmid

S23 GO-Line, S24 GO-Line,
S25 GO-Line (Speicherfeuerstätten)



A⁺



2,0
kW

ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

2015/1186

S23 GO-Line ceiling connection

Data sheet




Figure: S23 GO-Line with ceiling connection | Surface finish: Camina silicate paint

Standard	Total weight	Optional	Accessories		Storage concrete	Masonry stove
 hinged door, hinge on left / right  Front Kristall	 kg approx. 630 kg		 SMR	 Spark protection plate	 Storage concrete	 Ekko GO 45(45)57 with rotary chimney Nominal heat output: 2.0 kW Outlet for flue pipe: Ø 160 mm  A+ Energy efficiency class as per (EU) 2015/1186 More information at www.camina-schmid.de


S23 GO-Line ceiling connection

Dimensional drawing


Front view, scale 1:20




Left side view scale 1:20



Top view, scale 1:20



Screed recess (view of underside) scale 1:20



Note on left side view scale 1:20: AS (FGC): Flue gas connector, VLS (CAC): Combustion air connector, VLZ (CAS): Combustion air supply, OKFF (FFL): Finished floor level

Please note the information on **optional accessories** in our price list.

Illustrations are similar. All photos and drawings are protected by copyright. Usage or publication, even of individual details, is only permitted with our authorisation. There may be modifications to the colour and technical details caused by ongoing developments; subject to errors and omissions. Dated: 04/2020

Product data sheet

Regulation (EU) 2015/1186 supplementing Directive 2010/30/EU

	S23 GO-Line (Speicherfeuerstätte)
Supplier's name:	Camina & Schmid Feuerdesign und Technik GmbH & Co. KG
Supplier's model identifier:	S23 GO-Line (Speicherfeuerstätte)
Energy efficiency class:	A+
Direct heat output (kW)	2,0
Indirect heat output (kW):	–
Energy efficiency index (EEI):	115,1
Energy efficiency at nominal heat output (%):	86,3
Notes for specific precautions, installation or maintenance:	Please note the reference in the assembly instructions and operating manuals!

There may be modifications to technical details caused by ongoing developments; subject to errors and omissions. Dated: 11/2021



ENERG
енергия · ενέργεια




Camina  Schmid

S23 GO-Line, S24 GO-Line,
S25 GO-Line (Speicherfeuerstätten)



A⁺



2,0
kW

ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

2015/1186