

Declaration of Performance according to Regulation (EU) 305/2011

No.: LE3625



- | | |
|--|--|
| 1. Product | Creation 11 |
| 2. Intended use | space heating in residential buildings |
| 3. Trade mark | Camina & Schmid Feuerdesign und Technik GmbH & Co. KG
Maschweg 38 49324 D-Melle |
| 4. Authorized representative | - |
| 5. System of assessment and verification
of constancy of performance of the
construction product | system 3 |
| 6. The notified laboratory | notified body number: 3102 performed of the product type on the
basis of type testing under system 3. Test report No.: R-10043401300006-1 |
| 7. Harmonized technical specification | EN 16510-2-2 |

8. Essential characteristics

Safety in case of fire		
Minimum distance to combustible materials: ceiling (with active surface) (d_C) from the air inlet grille (with inactive surface) (d_{CC}) rear and side (between the insulation and the test wall) (d_R) rear and side (between the insulation and the insert) (d_{RS}) side radiation area front glass (d_L) side radiation area side glass (d_{LS}) to adjacent combustible materials front glass (d_P) to adjacent combustible materials side glass (d_{PS}) distance on the floor to the front (d_F) distance on the floor to the side (d_{FS}) distance below the fireplace (d_B)	d_C > 500 mm d_{CC} > 500 mm d_R 0 mm d_{RS} 120 mm d_L 0 mm d_{LS} 0 mm d_P 800 mm d_{PS} 0 mm d_F 0 mm d_{FS} 0 mm d_B > 150 mm	
Hygiene, health, environment		
Emissions related to 13% O ₂ CO NOx OGC PM	nominal heat output ≤ 1250 mg/m ³ ≤ 200 mg/m ³ ≤ 120 mg/m ³ ≤ 40 mg/m ³	partial load heat output NPD NPD NPD NPD
Safety and accessibility in use		
Data for installation to a chimney at Flue gas outlet temperature Minimum flue draught Flue gas mass flow	nominal heat output 257 °C 12 Pa 11,8 g/s	partial load heat output NPD NPD NPD
Data for installation to a chimney regarding fire safety on safety test heat output		
Fire safety of installation to the chimney	T400 G	
Energy economy and heat retention		
Appliance's thermal output and energy efficiency at Room heat output Water heat output Efficiency	nominal heat output 11 kW NPD > 80 %	partial load heat output NPD NPD NPD
Space heating efficiency		
Seasonal space heating efficiency at nominal heat output Energy-Efficiency Index (EEI) Energy-Efficiency class (A++ to G)	65 % 110 A+	
Sustainable use of natural resources		
Environmental sustainability	NPD	

9. The performance of the product is in conformity with the declared performance in point 8.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed on behalf of the manufacturer

Colin Rokossa | Managing Director
Melle, 01.10.2026