

## Declaration of Performance according to Regulation (EU) 305/2011

No.: LE0055826/3



1. Product: Profi K / R / Plus 12, Profi 12
2. Intended use: space heating in residential buildings
3. Trade mark: Camina & Schmid Feuerdesign und Technik GmbH & Co. KG  
Maschweg 38 | 49324 D-Melle
4. Authorized representative: -
5. System of assessment and verification of constancy of performance of the construction product: system 3
6. The notified laboratory: notified body number: 1015 performed of the product type on the basis of type testing under system 3. Test report No.: CPR-B-00558-26
7. Harmonized technical specification: EN 16510-2-2

## 8. Essential characteristics

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                          |                                                                                     |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Safety in case of fire                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                                                                                                          |                                                                                     |
| Minimum distance to combustible materials:<br>ceiling (with active surface) ( $d_c$ )<br>from the air inlet grille (with inactive surface) ( $d_{cc}$ )<br>rear and side (between the insulation and the test wall) ( $d_R$ )<br>rear and side (between the insulation and the insert) ( $d_{RS}$ )<br>side radiation area front glass ( $d_L$ )<br>side radiation area side glass ( $d_{LS}$ )<br>to adjacent combustible materials front glass ( $d_P$ )<br>to adjacent combustible materials side glass ( $d_{PS}$ )<br>distance on the floor to the front ( $d_F$ )<br>distance on the floor to the side ( $d_{FS}$ )<br>distance below the fireplace ( $d_B$ ) | $d_c$ > 500 mm<br>$d_{cc}$ > 500 mm<br>$d_R$ 0 mm<br>$d_{RS}$ 120 mm<br>$d_L$ 400 mm<br>$d_{LS}$ 0 mm<br>$d_P$ 1100 mm<br>$d_{PS}$ 0 mm<br>$d_F$ 0 mm<br>$d_{FS}$ 0 mm<br>$d_B$ > 150 mm |  |
| Hygiene, health, environment                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                          |                                                                                     |
| Emissions related to 13% O <sub>2</sub><br>CO<br>NOx<br>OGC<br>PM                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | nominal heat output<br>≤ 1250 mg/m <sup>3</sup><br>≤ 200 mg/m <sup>3</sup><br>≤ 120 mg/m <sup>3</sup><br>≤ 40 mg/m <sup>3</sup>                                                          | partial load heat output<br>NPD<br>NPD<br>NPD<br>NPD                                |
| Safety and accessibility in use                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                          |                                                                                     |
| Data for installation to a chimney at<br>Flue gas outlet temperature<br>Minimum flue draught<br>Flue gas mass flow                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | nominal heat output<br>212 °C<br>12 Pa<br>16,3 g/s                                                                                                                                       | partial load heat output<br>NPD<br>NPD<br>NPD                                       |
| Data for installation to a chimney regarding fire safety on safety test heat output                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                          |                                                                                     |
| Fire safety of installation to the chimney                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | T400 G                                                                                                                                                                                   |                                                                                     |
| Energy economy and heat retention                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                          |                                                                                     |
| Appliance's thermal output and energy efficiency at<br>Room heat output<br>Water heat output<br>Efficiency                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | nominal heat output<br>12,3 kW<br>NPD<br>> 80 %                                                                                                                                          | partial load heat output<br>NPD<br>NPD<br>NPD                                       |
| Space heating efficiency                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                                                                          |                                                                                     |
| Seasonal space heating efficiency at nominal heat output<br>Energy-Efficiency Index (EEI)<br>Energy-Efficiency class (A++ to G)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 65 %<br>111<br>A+                                                                                                                                                                        |                                                                                     |
| Sustainable use of natural resources                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                          |                                                                                     |
| Environmental sustainability                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | NPD                                                                                                                                                                                      |                                                                                     |

9. The performance of the product is in conformity with the declared performance in point 8.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed on behalf of the manufacturer

Colin Rokossa | Managing Director  
Melle, 01.10.2026