Declaration of Performance according to Regulation (EU) 305/2011
No.: LE1425

Camina Schmid

1. Product — Ekko 84(34)
2. Intended use — space heating in residential buildings
3. Trade mark — Camina & Schmid Feuerdesign und Technik GmbH & Co. KG
   Maschweg 38 | 49324 D-Melle
4. Authorized representative — -
5. System of assessment and verification of constancy of performance of the construction product — system 3
6. The notified laboratory — notified body number: 1015 performed of the product type on the basis of type testing under system 3. Test report No.: 1015-AoP-30-18155/TZ
7. Harmonized technical specification — EN 16510-2-2
8. Essential characteristics

| | | |
|---|---|---|
| *Safety in case of fire* | | |
| Minimum distance to combustible materials: | | |
| Ceiling (with active surface) ($d_C$) | $d_C$ > 500 mm | |
| from the air inlet grille (with inactive surface) ($d_{CC}$) | $d_{CC}$ > 500 mm | |
| rear and side (between the insulation and the test wall) ($d_R$) | $d_R$ 0 mm | |
| rear and side (between the insulation and the insert) ($d_{RS}$) | $d_{RS}$ 90 mm | |
| side radiation area front glass ($d_L$) | $d_L$ 840 mm | |
| side radiation area side glass ($d_{LS}$) | $d_{LS}$ 0 mm | |
| to adjacent combustible materials front glass ($d_P$) | $d_P$ 1200 mm | |
| to adjacent combustible materials side glass ($d_{PS}$) | $d_{PS}$ 1000 mm | |
| distance on the floor to the front (lower edge glass to floor 400 mm) ($d_F$) | $d_F$ 0 mm | |
| distance on the floor to the side (lower edge glass to floor 400 mm) ($d_{FS}$) | $d_{FS}$ 0 mm | |
| distance belowe the fireplace ($d_B$) | $d_B$ > 150 mm | |
| *Hygiene, health, environment* | | |
| Emissions related to 13% $O_2$ | nominal heat output | partial load heat output |
| CO | ≤ 1250 mg/m³ | NPD |
| NOx | ≤ 200 mg/m³ | NPD |
| OGC | ≤ 120 mg/m³ | NPD |
| PM | ≤ 40 mg/m³ | NPD |
| *Safety and accessibility in use* | | |
| Data for installation to a chimney at | nominal heat output | partial load heat output |
| Flue gas outlet temperature | 302 °C | NPD |
| Minimum flue draught | 12 Pa | NPD |
| Flue gas mass flow | 8,6 g/s | NPD |
| *Data for installation to a chimney regarding fire safety on safety test heat output* | | |
| Fire safety of installation to the chimney | T400 G | |
| *Energy economy and heat retention* | | |
| Appliance's thermal output and energy efficiency at | nominal heat output | partial load heat output |
| Room heat output | 7 kW | NPD |
| Water heat output | NPD | NPD |
| Efficiency | > 78 % | NPD |
| *Space heating efficiency* | | |
| Seasonal space heating efficiency at nominal heat output | 65 % | |
| Energy-Efficiency Index (EEI) | 103,4 | |
| Energy-Efficiency class (A++ to G) | A | |
| *Sustainable use of natural resources* | | |
| Environmental sustainability | NPD | |

9. The performance of the product is in conformity with the declared performance in point 8.
   This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed on behalf of the manufacturer

.....

Colin Rokossa | Managing Director
Melle, 01.10.2026