Declaration of Performance according to Regulation (EU) 305/2011
No.: LE925

Camina Schmid

1. Product — Lina / Lina TV 100
2. Intended use — space heating in residential buildings
3. Trade mark — Camina & Schmid Feuerdesign und Technik GmbH & Co. KG
   Maschweg 38 | 49324 D-Melle
4. Authorized representative — -
5. System of assessment and verification of constancy of performance of the construction product — system 3
6. The notified laboratory — notified body number: 1015 performed of the product type on the basis of type testing under system 3. Test report No.: 1015-AoP-30-18158/TZ
7. Harmonized technical specification — EN 16510-2-2
8. Essential characteristics

Safety in case of fire		
Minimum distance to combustible materials:		
Ceiling (with active surface) (d_C)	d_C	> 500 mm
from the air inlet grille (with inactive surface) (d_{CC})	d_{CC}	> 500 mm
rear and side (between the insulation and the test wall) (d_R)	d_R	0 mm
rear and side (between the insulation and the insert) (d_{RS})	d_{RS}	100 mm
side radiation area front glass (d_L)	d_L	910 mm
side radiation area side glass (d_{LS})	d_{LS}	Lina 0 mm / Lina TV 10 mm
to adjacent combustible materials front glass (d_P)	d_P	1300 mm
to adjacent combustible materials side glass (d_{PS})	d_{PS}	0 mm
distance on the floor to the front (lower edge glass to floor 400 mm) (d_F)	d_F	0 mm
distance on the floor to the side (lower edge glass to floor 400 mm) (d_{FS})	d_{FS}	0 mm
distance belowe the fireplace (d_B)	d_B	> 240 mm

Hygiene, health, environment		
Emissions related to 13% O_2	nominal heat output	partial load heat output
CO	≤ 1250 mg/m³	NPD
NOx	≤ 200 mg/m³	NPD
OGC	≤ 120 mg/m³	NPD
PM	≤ 40 mg/m³	NPD
Safety and accessibility in use		
Data for installation to a chimney at	nominal heat output	partial load heat output
Flue gas outlet temperature	320 °C	NPD
Minimum flue draught	12 Pa	NPD
Flue gas mass flow	10,1 g/s	NPD
Data for installation to a chimney regarding fire safety on safety test heat output		
Fire safety of installation to the chimney	T400 G	
Energy economy and heat retention		
Appliance's thermal output and energy efficiency at	nominal heat output	partial load heat output
Room heat output	10 kW	NPD
Water heat output	NPD	NPD
Efficiency	> 78 %	NPD
Space heating efficiency		
Seasonal space heating efficiency at nominal heat output	65 %	
Energy-Efficiency Index (EEI)	103,4	
Energy-Efficiency class (A++ to G)	A	
Sustainable use of natural resources		
Environmental sustainability	NPD	

9. The performance of the product is in conformity with the declared performance in point 8.
   This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed on behalf of the manufacturer

.....

Colin Rokossa | Managing Director
Melle, 01.10.2026