

Declaration of Performance according to Regulation (EU) 305/2011

No.: LE94202



1. Product HK 80
2. Intended use space heating in residential buildings
3. Trade mark Camina & Schmid Feuerdesign und Technik GmbH & Co. KG
Maschweg 38 | 49324 D-Melle
4. Authorized representative -
5. System of assessment and verification of constancy of performance of the construction product system 3
6. The notified laboratory notified body number: 1879 performed of the product type on the basis of type testing under system 3. Test report No.: will follow
7. Harmonized technical specification EN 16510-2-2

8. Essential characteristics

Safety in case of fire		
Minimum distance to combustible materials: Ceiling (with active surface) (d_C) from the air inlet grille (with inactive surface) (d_{CC}) rear and side (between the insulation and the test wall) (d_R) rear and side (between the insulation and the insert) (d_{RS}) side radiation area front glass (d_L) side radiation area side glass (d_{LS}) to adjacent combustible materials front glass (d_P) to adjacent combustible materials side glass (d_{PS}) distance on the floor to the front (lower edge glass to floor 400 mm) (d_F) distance on the floor to the side (lower edge glass to floor 400 mm) (d_{FS}) distance below the fireplace (d_B)	d_C > 500 mm d_{CC} > 500 mm d_R 0 mm d_{RS} 80 mm d_L 500 mm d_{LS} 500 mm d_P 1000 mm d_{PS} 800 mm d_F 0 mm d_{FS} 0 mm d_B > 310 mm	
Hygiene, health, environment		
Emissions related to 13% O ₂ CO NOx OGC PM	nominal heat output ≤ 1250 mg/m ³ ≤ 200 mg/m ³ ≤ 120 mg/m ³ ≤ 40 mg/m ³	partial load heat output NPD NPD NPD NPD
Safety and accessibility in use		
Data for installation to a chimney at Flue gas outlet temperature Minimum flue draught Flue gas mass flow	nominal heat output 269 °C 12 Pa 8,6 g/s	partial load heat output NPD NPD NPD
Data for installation to a chimney regarding fire safety on safety test heat output		
Fire safety of installation to the chimney	T400 G	
Energy economy and heat retention		
Appliance's thermal output and energy efficiency at Room heat output Water heat output Efficiency	nominal heat output 8 kW NPD ≥ 80 %	partial load heat output NPD NPD NPD
Space heating efficiency		
Seasonal space heating efficiency at nominal heat output Energy-Efficiency Index (EEI) Energy-Efficiency class (A++ to G)	65 % 109,6 A+	
Sustainable use of natural resources		
Environmental sustainability	NPD	

9. The performance of the product is in conformity with the declared performance in point 8.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed on behalf of the manufacturer

Colin Rokossa | Managing Director
Melle, 01.10.2026